
NG500A

Inductive NAMUR sensor

IGB2012-N/US/1G/1D



Product characteristics		
Electrical design		NAMUR
Output function		normally closed
Sensing range	[mm]	12
Housing		threaded type
Dimensions	[mm]	M18 x 1 / L = 51
Application		
Application		For applications in hazardous areas
Electrical data		
Connection to switching amplifiers		yes
Switching amplifiers		connection to certified intrinsically safe circuits with the max. values: U = 15 V / I = 50 mA / P = 120 mW
Nominal voltage DC	[V]	8.2; (1kΩ)
Supply voltage DC	[V]	7.5...30; (when used outside the hazardous area)
Current consumption	[mA]	< 1; (disabled; conductive: > 2,1)
Protection class		II
Outputs		
Electrical design		NAMUR
Output function		normally closed
Permanent current rating of switching output DC	[mA]	30; (when used outside the hazardous area)
Switching frequency DC	[Hz]	300
Detection zone		
Sensing range	[mm]	12
Real sensing range Sr	[mm]	12 ± 10 %
Accuracy / deviations		
Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	1...15
Switch point drift	[% of Sr]	-10...10
Operating conditions		
Ambient temperature	[°C]	-20...70

NG500A

Inductive NAMUR sensor


IGB2012-N/US/1G/1D

Protection			IP 67
Tests / approvals			
Approval			BVS 04 ATEX E 091 X; IECEx BVS 06.0003X
ATEX marking			II 1G Ex ia IIC T6 Ga
			II 1D Ex ia IIIC T200 90°C Da
EMC		EN 60947-5-6	
Shock/vibration resistance			30 g (11 ms) / 10-55 Hz (1 mm)
MTTF	[years]		3387
Safety classification			
Max. internal capacitance	[nF]		200
Max. internal inductance	[µH]		85
Mechanical data			
Weight	[g]		90
Housing			threaded type
Mounting			non-flush mountable
Dimensions	[mm]		M18 x 1 / L = 51
Thread designation			M18 x 1
Materials			housing: brass special coating; sensing face: PBT; LED window: PA
Displays / operating elements			
Display		switching status	4 x 90° LED, yellow
Accessories			
Items supplied			lock nuts: 2
Remarks			
Pack quantity			1 pcs.
Electrical connection - plug			

Connector: 1 x M12; coding: A; Contacts: 4



Connection



1 = connection to NAMUR amplifiers