
IG6621

Inductive analogue sensor

IGK3008A1PKG/0,2M/PUR



Product characteristics		
Housing		threaded type
Dimensions	[mm]	M18 x 1 / L = 54
Electrical data		
Operating voltage	[V]	15...30 DC
Current consumption	[mA]	< 20
Protection class		II
Reverse polarity protection		yes
Outputs		
Analogue current output	[mA]	4...20; (linear; gradient: 2,22 mA/mm; for frontal approach and for target made of mild steel: 24 x 24 x 1 mm)
Max. load	[Ω]	500
Short-circuit protection		yes
Overload protection		yes
Detection zone		
Measuring range	[mm]	0.8...8
Accuracy / deviations		
Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Linearity error of analogue output	[%]	± 1 %; (of IA max)
Repeatability analogue output	[%]	± 1 %; (of IA max)
Response times		
Response time	[ms]	< 10
Operating conditions		
Ambient temperature	[°C]	-40...80
Protection		IP 67
Tests / approvals		
MTTF	[years]	952
Mechanical data		
Weight	[g]	79.06
Housing		threaded type
Mounting		non-flush mountable
Dimensions	[mm]	M18 x 1 / L = 54

IG6621


Inductive analogue sensor

IGK3008A1PKG/0,2M/PUR

Thread designation	M18 x 1	
Materials	housing: brass white bronze coated; sensing face: PBT	
Displays / operating elements		
Display	target in measuring range	yellow lights
	target outside measuring range	yellow flashing
Accessories		
Items supplied	lock nuts: 2	
Remarks		
Pack quantity	1 pcs.	
Electrical connection		

Cable: 0.2 m, PUR, Ø 4 mm; burning behaviour to ECE R118 rev. 2; 3 x 0.50 mm²
; flame-retardant (IEC 60332-2, UL: FT2)

Connection



	Core colours :
BK =	black
BN =	brown
BU =	blue