
# SI5006

## Flow monitor

SID10ADBFKOW/LS-100-IRF




1 LED bar display
2 setting pushbutton
3 Tightening torque 25 Nm

| | | | |
|---|---|---|---|
| **Product characteristics** | | | |
| Number of inputs and outputs | | Number of digital outputs: 1 | |
| Process connection | | threaded connection M18 x 1,5 internal thread | |
| **Application** | | | |
| Media | | Liquids; Gases | |
| Medium temperature | [°C] | -25...80 | |
| Pressure rating | | 300 bar | 30 MPa |
| MAWP for applications according to CRN | [bar] | 208 | |
| Liquids | | | |
| Medium temperature | [°C] | -25...80 | |
| Gases | | | |
| Medium temperature | [°C] | -25...80 | |
| **Electrical data** | | | |
| Frequency AC | [Hz] | 47...63 | |
| Operating voltage tolerance | [%] | -15...10 | |
| Operating voltage | [V] | 90...240 AC | |
| Max. power consumption | [VA] | 3.5 | |
| Protection class | | II | |
| Reverse polarity protection | | no | |
| Power-on delay time | [s] | 10 | |

# SI5006

## Flow monitor

SID10ADBFKOW/LS-100-IRF

| | | |
|---|---|---|
| **Inputs / outputs** | | |
| Number of inputs and outputs | | Number of digital outputs: 1 |
| **Outputs** | | |
| Total number of outputs | | 1 |
| Output signal | | switching signal |
| Electrical design | | relay |
| Number of digital outputs | | 1 |
| Output function | | normally open / normally closed; (parameterisable) |
| Contact rating | | 3 A (250 V AC / 30 V DC); (number of switching cycles: 20 million mechanically; switching cycles at 3 A load: 100,000 electrical; type of switch-off: normally open) |
| Short-circuit proof | | no |
| Overload protection | | no |
| **Measuring/setting range** | | |
| Probe length L | [mm] | 45 |
| Liquids | | |
| Setting range | [cm/s] | 3...300 |
| Greatest sensitivity | [cm/s] | 3...100 |
| Gases | | |
| Setting range | [cm/s] | 200...3000 |
| Greatest sensitivity | [cm/s] | 200...800 |
| **Accuracy / deviations** | | |
| Repeatability | [% of Sr] | 1...5 |
| Note on repeatability | | for water 5...100 cm/s; 25 °C<br>Factory setting |
| Temperature drift | [cm/s x 1/K] | 0.1; (for water 5...100 cm/s; 10...70 °C) |
| Temperature gradient | [K/min] | 300 |
| Switch point accuracy | [cm/s] | ± 2...± 10; (for water 5...100 cm/s; 25 °C; Factory setting) |
| Hysteresis | [cm/s] | 2...5; (for water 5...100 cm/s; 25 °C; Factory setting) |
| **Response times** | | |
| Response time | [s] | 1...10 |
| Liquids | | |
| Response time | [s] | 1...10 |
| Gases | | |
| Response time | [s] | 1...10 |
| **Software / programming** | | |
| Adjustment of the switch point | | pushbutton |
| **Operating conditions** | | |
| Ambient temperature | [°C] | -25...80 |
| Storage temperature | [°C] | -25...100 |
| Protection | | IP 67 |

# SI5006

## Flow monitor

SID10ADBFKOW/LS-100-IRF


| | | | |
|---|---|---|---|
| **Tests / approvals** | | | |
| EMC | | DIN EN 61000-6-2 | |
| | | DIN EN 61000-6-3 | |
| Shock resistance | | DIN EN 60068-2-27 | 50 g (11 ms) |
| Vibration resistance | | DIN EN 60068-2-6 | 18 g (55...2000 Hz) |
| MTTF | [years] | 221 | |
| **Mechanical data** | | | |
| Weight | [g] | 262.5 | |
| Housing | | cylindrical | |
| Dimensions | [mm] | Ø 50 / L = 113 | |
| Materials | | stainless steel (316L/1.4404); stainless steel (304/1.4301); PC; PBT-GF20; EPDM/X | |
| Materials (wetted parts) | | stainless steel (316L/1.4404); O-ring: FKM 80 Shore A | |
| Process connection | | threaded connection M18 x 1,5 internal thread | |
| Probe diameter | [mm] | 8.2 | |
| Installation length EL | [mm] | 45 | |
| **Displays / operating elements** | | | |
| Display | function | 10 x LED, three-colour | |
| **Electrical connection** | | | |
| Required protection | | miniature fuse to IEC60127-2 sheet 1; ≤ 5 A; fast acting | |
| **Remarks** | | | |
| Remarks | | Recommendation Check the safe functioning of the unit after a short circuit. | |
| Pack quantity | | 1 pcs. | |

## Electrical connection

Connector: 1 x 1/2"; coding: C; Contacts: 5




### Connection




Note miniature fuse to IEC60127-2 sheet 1 ≤ 5 A fast acting